

Gauges



Deluxe

Hourmeter black face

06397-ZW5-U10

- Analogue display, 9999 hours, flat lens, drilling diameter 53MM
- Required parts: 32540-ZV5-911, 32550-ZW5-U00

Application: BF25D to BF225AK1



Hourmeter white face

06397-ZW5-U00

- Analogue display, 9999 hours, flat lens, drilling diameter 53MM
- Required parts: 32540-ZV5-911, 32550-ZW5-U00

Application: BF25D to BF225AK1



Speedometer

06373-ZW5-U11

- Black face, white italic letters & needle 10-50 mph (20-80 km/h), flat lens, drilling diameter 86MM
- Required parts: 32540-ZV5-911, 32550-ZW5-U00

Application: BF25D to BF225AK1



Speedometer

06373-ZW5-U01

- White face, black italic letters & needle 10-50 mph (20-80 km/h), flat lens, drilling diameter 86MM
- Required parts: 32540-ZV5-911, 32550-ZW5-U00

Application: BF25D to BF225AK1



Gauges



Deluxe

Tachometer

06375-ZW5-U11

- Black face, white italic letters & needle 0-7000 rpm, flat lens, drilling diameter 81MM
- Required part: 32540-ZV5-911

Application: BF25D to BF225AK1



Tachometer

06375-ZW5-U01

- White face, black italic letters & needle 0-7000 rpm, flat lens, drilling diameter 81MM
- Required part: 32540-ZV5-911

Application: BF25D to BF225AK1



Trim meter

06372-ZW5-U11

- Black face, white markings & needle
- Up & down indicator, flat lens, drilling diameter 53MM
- Required part: 32540-ZV5-911

Application: BF25D to BF225AK1



Trim meter

06372-ZW5-U01

- White face, black markings & needle
- Up & down indicator, flat lens, drilling diameter 53MM
- Required part: 32540-ZV5-911

Application: BF25D to BF225AK1



Gauges



Deluxe

Voltmeter

06374-ZW5-U10

- Black face, white italic letters & needle
- 8-16 volts indicator, flat lens, drilling diameter 53MM
- Required parts: 32540-ZV5-911, 32550-ZW5-U00

Application: BF25D to BF225AK1



Voltmeter

06374-ZW5-U00

- White face, black italic letters & needle
- 8-16 volts indicator, flat lens, drilling diameter 53MM
- Required parts: 32540-ZV5-911, 32550-ZW5-U00

Application: BF25D to BF225AK1



Tachometer

37250-ZV5-823

- 0-7000 rpm, black face, flat lens, white letters & yellow needle, drilling diameter 81MM
- Required part: 32540-ZV5-911

Application: BF40A / BF50A, BF40D / BF50D



Tachometer

37250-ZV7-912

- 0-7000 rpm, black face, flat lens, white letters & yellow needle, drilling diameter 81MM
- Required part: 32540-ZV5-911

*Application: BF20 / 25/30A, BF25 / 30D
BF60 to BF225AK1*



Gauges



Deluxe

Tachometer

37250-ZW9-901

- 0-7000 rpm, black face, flat lens, white letters & yellow needle, drilling diameter 81MM
- Required part: 32540-ZV5-911

Application: BF8D to BF20D



Trim meter

37260-ZV5-822

- Up & down indicator, black face, flat lens, white markings & yellow needle, drilling diameter 53MM
- Required part: 32540-ZV5-911

Application: BF40 to BF225



Speedometer

06372-ZV5-950AH

- 5-35 mph (10-55 km/h)
- Black face, flat lens, white letters & yellow needle, drilling diameter 86MM
- Required parts: 32540-ZV5-911 and 32550-ZV5-910

Application: BF40 to BF225



Tachometer

37250-ZV5-950AH

- 0-7000 rpm, black face, flat lens, white letters & yellow needle, drilling diameter 86MM
- Required part: 32540-ZV5-911

Application: BF20A to BF225



Gauges



Deluxe

Hourmeter

39700-ZV5-800AH

- Digital 0-9999 hours indicator, 2 operating modes resettable
- Black face, flat lens, drilling diameter 53MM
- Required parts: 32540-ZV5-911 and 32550-ZV5-910

*Application: BF20A to BF225
Does not work with BF25 to BF50A4
(tiller handle models)*



Dual assy meter with Tacho/Hour meter function

08174-ZL8-000HE

- A five digit LCD display reads up to 99999 rpm in 20 rpm increments and displays up to 9999.9 hours of engine operation before resetting to zero

Application: BF2 to BF20



Rudder meter Kit white

06373-ZZ3-000

- Rudder meter allows the operating angle of the motor to be determined easily without looking behind or if the motor is obstructed from view.
- Recommended for use with Deluxe gauge Pre Rigging kits

Application: BF60A, BFP60A



Rudder meter Kit black

06373-ZZ3-610

- Rudder meter allows the operating angle of the motor to be determined easily without looking behind or if the motor is obstructed from view.
- Recommended for use with Deluxe gauge Pre Rigging kits

Application: BF60A, BFP60A



Gauges



Fog Resistant

US Instrument set

06303-ZW5-000ZB

- White face, black letters & red illuminated needle
- Includes 5 gauges: 0-7000rpm / digital hour meter, 10-65 mph / 20-100 km/h speedometer, 8-18 voltmeter, 240-33 ohms fuel gauge, trim meter, drilling diameter 86MM (rpm & speed) and 53MM (volt, fuel, trim), domed lens
- Required part: 32200-ZW7-000AH



Application: BF25 to BF225

US Instrument set

06303-ZW5-000ZA

- Black face, white letters & white illuminated needle
- Includes 5 gauges: 0-7000rpm / digital hour meter, 10-65 mph / 20-100 km/h speedometer, 8-18 voltmeter, 240-33 ohms fuel gauge, trim meter, drilling diameter 86MM (rpm & speed) and 53MM (volt, fuel, trim), domed lens
- Required part: 32200-ZW7-000AH



Application: BF25 to BF225

EU Instrument set

06304-ZW5-000ZB

- White face, black letters & red illuminated needle
- Includes 5 gauges: 0-7000rpm / digital hour meter, 10-65 mph / 20-100 km/h speedometer, 8-18 voltmeter, 10-180 ohms fuel gauge, trim meter, drilling diameter 86MM (rpm & speed) and 53MM (volt, fuel, trim), domed lens
- Required part: 32200-ZW7-000AH



Application: BF25 to BF225

EU Instrument set

06304-ZW5-000ZA

- Black face, white letters & white illuminated needle
- Includes 5 gauges: 0-7000rpm / digital hour meter, 10-65 mph / 20-100 km/h speedometer, 8-18 voltmeter, 10-180 ohms fuel gauge, trim meter, drilling diameter 86MM (rpm & speed) and 53MM (volt, fuel, trim), domed lens
- Required part: 32200-ZW7-000AH



Application: BF25 to BF225

Gauges



Fog Resistant

Speedometer

37203-ZW5-000ZB

- White face, black letters & red illuminated needle
- 10-65mph / 20-100 km/h, domed lens, drilling diameter 86MM
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Speedometer

37203-ZW5-000ZA

- Black face, white letters & white illuminated needle
- 10-65mph / 20-100 km/h, domed lens, drilling diameter 86MM
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Tacho / hourmeter

37253-ZW5-000ZB

- White face, black letters & red illuminated needle
- 0-7000 rpm & digital hour meter, domed lens, drilling diameter 86MM
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Tacho / hourmeter

37253-ZW5-000ZA

- Black face, white letters & white illuminated needle
- 0-7000 rpm & digital hour meter, domed lens, drilling diameter 86MM
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Gauges



Fog Resistant

Trim meter

37263-ZW5-000ZB

- White face, black letters & red illuminated needle
- Up & down indicator, domed lens, drilling diameter 53MM
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Trim meter

37263-ZW5-000ZA

- Black face, white letters & white illuminated needle
- Up & down indicator, domed lens, drilling diameter 53MM
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Voltmeter

37453-ZW5-000ZB

- White face, black letters & red illuminated needle
- 8-18 volts indicator, domed lens, drilling diameter 53MM
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Voltmeter

37453-ZW5-000ZA

- Black face, white letters & white illuminated needle
- 8-18 volts indicator, domed lens, drilling diameter 53MM
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Gauges



Fog Resistant

US Fuel meter

37303-ZW5-000ZB

- White fuel meter domed lens, black letters & red illuminated needle.
- For inbuilt fuel tanks
- Drilling diameter 53MM
- Ohms 240 Ω (empty) to 33 Ω (full) scale

Application: BF25 to BF225



US Fuel meter

37303-ZW5-000ZA

- Black fuel meter domed lens, white letters & white illuminated needle.
- For inbuilt fuel tanks
- Drilling diameter 53MM
- Ohms 240 Ω (empty) to 33 Ω (full) scale

Application: BF25 to BF225



EU Fuel meter

37304-ZW5-000ZB

- White fuel meter domed lens, black letters & red illuminated needle.
- For inbuilt fuel tanks
- Drilling diameter 53MM
- Ohms 10 Ω (empty) to 180 Ω (full) scale

Application: BF25 to BF225



EU Fuel meter

37304-ZW5-000ZA

- Black fuel meter domed lens, white letters & white illuminated needle.
- For inbuilt fuel tanks
- Drilling diameter 53MM
- Ohms 10 Ω (empty) to 180 Ω (full) scale

Application: BF25 to BF225



Gauges



Fog Resistant

Water pressure meter

37353-ZW5-000ZB

- White face, black letters & red illuminated needle
- 0-30PSI scale, including tubing and engine fitting, domed lens, drilling diameter 53MM
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Water pressure meter

37353-ZW5-000ZA

- Black face, white letters & white illuminated needle
- 0-30PSI scale, including tubing and engine fitting, domed lens, drilling diameter 53MM
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Gauges



Fog Resistant - Charcoal grey

Instrument set

06300-ZW5-003SK

- Charcoal grey, Chromed ring, black letters & red illuminated needle
- Includes 4 gauges: 0-7000rpm / digital hour meter, 10-50 knots speedometer, 240-33 ohms fuel gauge, trim meter, drilling diameter 86MM (rpm & speed) and 53MM (fuel, trim), domed lens
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Speedometer

37200-ZW5-003SK

- Charcoal grey, chromed ring, black letters & red illuminated needle
- 10-50 knots, domed lens, drilling diameter 86MM
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Tacho / hourmeter

37250-ZW5-003SK

- Charcoal grey, black letters & red illuminated needle
- 0-7000rpm & digital hour meter, domed lens, drilling diameter 86MM
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Trim meter

37260-ZW5-003SK

- Charcoal grey, black letters & red illuminated needle
- Up & down indicator, domed lens, drilling diameter 53MM
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Gauges



Fog Resistant - Charcoal grey

US Fuel meter

37300-ZW5-003SK

- Charcoal grey fuel meter domed lens, black letters & red illuminated needle
- For inbuilt fuel tanks
- Drilling diameter 53MM
- Ohms 240 Ω (empty) to 33 Ω (full) scale

Application: BF25 to BF225



Voltmeter

37450-ZW5-003SK

- Charcoal grey, Chromed ring, black letters & red illuminated needle
- 10-16 volts indicator, domed lens, drilling diameter 53MM
- Required part: 32200-ZW7-000AH

Application: BF25 to BF225



Gauges



Notes

A series of horizontal dotted lines for taking notes, spanning the width of the page.